Product specifications

Eaton 35FE

Catalog Number: 35FE

Eaton Bussmann series high speed British standard fuse, Single barrel, 35A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC



General specifications

Product Name
Eaton Bussmann series high speed british standard fuse

Catalog Number
35FE

UPC
051712834186

EAN
5027590477727

Product Length/Depth
76 mm

Product Height
20 mm

Product Width
20 mm

Product Weight
41.4 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
IEC Rated
UL Recognized
Designed and tested to BS88 part 4
IEC 60269-4

Powering Business Worldwide

Electrical data

Amperage Rating

35 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

500 V

Interrupt rating

200 kA RMS Sym, 50 kA at 500 Vdc

Class

Class aR

Pre arc (I2T)

33

Clearing (I2T)

130 at 415 V, 200 at 660 V

Watt losses

9 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatble Trip indicator/Microswitch

Suitable for

EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Certification reports

DA-DC-00004685

DA-DC-00004682

Technical data sheets

720024 CT, ET, FE, EET, FEE, FM, FMM, MT, MMT fuses



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia