Specifications



Photo is representative





Eaton BK/SC-2

Eaton Bussmann series SC fuse, Current-limiting fast acting fuse, Rejection style, 2 A, Class G, Non-indicating, Ferrule end x ferrule end, 10 kAIC at 170 Vdc, 100 kAIC at 600 Vac, Bulk, 600 V, 170 Vdc

General specifications	
PRODUCT NAME	Eaton Bussmann series SC fuse
CATALOG NUMBER	BK/SC-2
UPC	051712750387
EAN	5027590408356
PRODUCT LENGTH/DEPTH	0.41 in
PRODUCT HEIGHT	1.31 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.1 lb
WARRANTY	Not Applicable
COMPLIANCES	Not Applicable RoHS Compliant
CATALOG NOTES	Bulk

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	2 A
INTERRUPT RATING	100 kAIC at 600 Vac 10 kAIC at 170 Vdc
VOLTAGE RATING	600 Vac, 170 Vdc

Physical details

PACKAGING TYPE	Standard Bulk

General information

CLASS	Class G
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Rejection style

Resources

CATALOGS	BK/SC-2~BK-SC-2~BUSS SC FUSE CLASS G Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BK/SC-2

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.