Product specifications

Eaton 170M1558D

Catalog Number: 170M1558D

Fuse-link, high speed, 10 A, AC 690 V, DIN 000, gR, DIN, IEC, dual indicator, live gripping lugs

General specifications

Product Name
Eaton Bussmann series high speed square body fuse

Catalog Number
170M1558D

UPC
051712334891

EAN
5027590441179

Product Length/Depth
79 mm

Product Height
51 mm

Product Width
21 mm

Product Weight
134.7 g

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
IEC Rated
UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

10 A

Breaking capacity

200 kA

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

gR (general purpose semiconductor protection)

Voltage type

AC

Fuse size

000

Rated voltage AC

690 V

Current type

AC

Class

Class gR

Clearing (I2T)

27 at 660 V

Watt losses

2.5 W

Fuse shape

Square body, knife blade contacts

Pre arc (I2T)

4

Color

None

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA NH-style, high-speed dual indicator fuselinks

CE NH-style, high-speed dual indicator fuselinks

Installation videos

Eaton's Switch disconnectors and Bussmann series fuses for MOEM Applications (brightcove.net)

Technical data sheets

720101 DIN 43620 690V Dual ind

Interrupt rating

200 kAIC

Fitted with:

Dual indicator

Connection

Din 43-620 blade end x Din 43-620 blade end

Construction size

000

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43620

Bladed

Fuse system (according to IEC 60269)

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia