Product specifications

Eaton V48M28T4916SS



Photo is representative

Catalog Number: V48M28T4916SS

150 kVA DOE 2016 Ventd XFMR 3PH 480-208Y/120, 150 °C rise, Aluminum,

General specifications

Product Name
Eaton General purpose ventilated transformer

Catalog Number
V48M28T4916SS

UPC
786680230431

Product Length/Depth
31.5 in

Product Height
51 in

Product Width
34.5 in

Product Weight
1342 lb

Compliances
DOE2016 Efficient

Certifications
UL Listed

Catalog Notes
66 CFR Part 431 (2016) Efficient

Powering Business Worldwide

Physical Attributes

Coil material
Aluminum

Enclosure
NEMA 2

Frame
FR943

Insulation
220 °C

Mounting
Floor or wall

Tap size
2 at +2.5%, 4 at -2.5%

Type
Energy-efficient ventilated transformer

Wiring connection
280B

Performance Ratings

Efficiency
10 CFR Part 431-2016 (DOE 2016)

Frequency rating
60 Hz

Kva Rating
150 kVA

Primary voltage
480 V

Secondary Voltage
208Y/120 V

Sound Level
NEMA ST-20

Temperature rise
150 °C rise

Volt ampere rating
150 kVA

Miscellaneous

Modification 1
304 stainless steel enclosure

Weathershield
943

Resources

Brochures

Eaton's low-voltage dry-type distribution transformers

Eaton's high-efficiency dry-type transformers

Specifications and datasheets

Eaton Specification Sheet - V48M28T4916SS

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia