Specifications



Photo is representative





Eaton CPH7733

Eaton Crouse-Hinds series Arktite CPH plug, 30A/60A, 0.500-0.875" cable diameter, 2-wire, 3-pole, Brass or hard-drawn copper contacts, Style 2, 3 HP, Copper-free alum, Single-phase, Mechanical cable grip and neoprene bush, 120-240/480 Vac

General specifications	
PRODUCT NAME	Eaton Crouse-Hinds series Arktite CPH plug
CATALOG NUMBER	CPH7733
UPC	782274173405
PRODUCT LENGTH/DEPTH	7.75 in
PRODUCT HEIGHT	2.75 in
PRODUCT WIDTH	2.75 in
PRODUCT WEIGHT	1.85 lb

Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 1 Class I, Division 2

Product specifications

GROUNDING STYLE	Style 2
CONFIGURATION	Two-wire, three-pole
PHASE	Single-phase
HORSEPOWER	3 hp
AMPERAGE RATING	30A/60A
VOLTAGE RATING	120-240 Vac/480 Vac
CABLE DIAMETER	0.500-0.875 in
MATERIAL	Copper-free aluminum
CONTACT MATERIAL	Brass Hand-drawn copper
SPECIAL FEATURES	Mechanical cable grip and neoprene bushing

Resources

CATALOGS	Arktite CES and CPH Explosionproof Receptacles and Plugs catalog page
CERTIFICATION REPORTS	Arktite CES and CPH Explosionproof Receptacles and Plugs Canadian certification Arktite CES and CPH Explosionproof Receptacles and Plugs UL certification
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CPH7733

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.