Specifications



Photo is representative

Eaton V3LM2CHF2/UNV1

Eaton Crouse-Hinds series Vaporgard V2L LED, 0.24A, Cool white, AC drive, 50W HID or 150-200W incan equiv, 50/60 Hz, Without guard, Heat and impact resistant glass lens, 3000 lm, Copper-free alum, Ceil w/ junct box, 3/4", 120-277 Vac, 29W

General specifications	
PRODUCT NAME	Eaton Crouse-Hinds series Vaporgard V2L LED light fixture
CATALOG NUMBER	V3LM2CHF2/UNV1
UPC	662276652200
PRODUCT LENGTH/DEPTH	8.75 in
PRODUCT HEIGHT	5.75 in
PRODUCT WIDTH	8.75 in
PRODUCT WEIGHT	6.8 lb

Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	NEC/CEC
NEC HAZARDOUS RATING	Class I, Division 2
NEMA RATING	4X
INGRESS PROTECTION (IP) RATINGS	IP66

Product specifications

LUMENS	3000
COLOR TEMPERATURE	Cool white
MOUNTING METHOD	Ceiling with junction box
TRADE SIZE	3/4"
VOLTAGE RATING	120-277 Vac
DRIVE TYPE	AC
FREQUENCY RATING	50/60 Hz
LENS MATERIAL	Heat and impact resistant glass
WATTAGE	29W
AMPERAGE RATING	0.24 A
MATERIAL	Copper-free aluminum
POWER FACTOR	> 0.9
GUARD	Without guard
EQUIVALENT LUMINAIRE	50W HID or 150-200W incandescent

Resources

BROCHURES	Crouse-Hinds series Vaporgard V2L/V3L LED brochure Crouse-Hinds series Global LED lighting portfolio
CATALOGS	Crouse-Hinds series Vaporgard V2L/V3L LED catalog page
CERTIFICATION REPORTS	Vaporgard V2L Hazardous Area LED Light Fixtures Canadian certification Vaporgard V2L Hazardous Area LED Light Fixtures UL certification
INSTALLATION INSTRUCTIONS	IF 1885 - Vaporgard V2L/V3L Driver Modules - AC Version
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - V3LM2CHF2/UNV1

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.