Specifications



Photo is representative





Eaton TRNP24AD

Eaton TR Series Timing Relay, Pin/octal style terminals, Power triggered, 24 Vac/dc coil, 50/60 Hz, 10A, 240 Vac/30 Vdc max. allowable load, 2 form C, DPDT (delayed output) contact configuration

General specifications	
PRODUCT NAME	Eaton TR timing relay
CATALOG NUMBER	TRNP24AD
UPC	782116149865
PRODUCT LENGTH/DEPTH	3.07 in
PRODUCT HEIGHT	1.58 in
PRODUCT WIDTH	1.42 in
PRODUCT WEIGHT	0.6 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	TUV CE Marked
CERTIFICATIONS	cULus Listed CSA Certified

Powering Business Worldwide

Product specifications

PROD LOAD	10A, 240 Vac/30 Vdc
FREQUENCY RATING	50-60 Hz
COIL VOLTAGE	24 Vac/dc
OPERATING MODE	Power triggered
CONTACT CONFIGURATION	2 form C, DPDT
TERMINALS	Pin, octal
SERIES	TR
FUNCTIONS	ON delay Single shot leading edge voltage controlled Flasher-pause or ON first Power triggered
OUTPUT	Delayed

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - TRNP24AD
WARRANTY GUIDES	Selling Policy 25-000 - Distribution and Control Products and Services

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.