# Specifications



**Photo is representative**





## Eaton D7PF2AT1

D7 Series General Purpose Plug-In Relay, Full featured cover, 24 Vdc coil, 650 Ohms resistance, Plug-in terminal, DPDT contact configuration, 15A contact rating, Silver alloy contacts, IP40 enclosure

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton General-purpose relay |
| **CATALOG NUMBER** | D7PF2AT1 |
| **UPC** | 782116484829 |
| **PRODUCT LENGTH/DEPTH** | 2 in |
| **PRODUCT HEIGHT** | 1 in |
| **PRODUCT WIDTH** | 1 in |
| **PRODUCT WEIGHT** | 0.06 lb |
| **WARRANTY** | Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |
| **COMPLIANCES** | RoHS Compliant<br>CE Marked |
| **CERTIFICATIONS** | UL Listed file E37317<br>CSA file No. LR217069<br>cRUus<br>UL Listed file E65657<br>CSA file No. LR217017 |
| **PRODUCT TYPE** | General-purpose relay |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **TYPE** | General-purpose relay |
| **COVER** | Full featured |
| **OPTIONS** | LED test button, flag indicator, lock-down door, finger-grip cover, ID tag |
| **COIL VOLTAGE** | 24 Vdc |
| **CONTACT CONFIGURATION** | DPDT |
| **CONTACT MATERIAL** | Silver alloy |
| **CONTACT RATING** | 15 A |
| **ENCLOSURE** | IP40 |
| **RESISTANCE** | 650 Ω |
| **SERIES** | D7 |
| **TERMINALS** | Plug-in |
| **VOLTAGE - MAX** | 300 V switching |

## Resources

| | |
|---|---|
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - D7PF2AT1 |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.