Specifications



Photo is representative





Eaton D4PR2T1

Eaton General-purpose relay, D4 Series, QTY: 1, 24 Vdc coil, DPDT contact configuration, 5 A, 240 Vac/30 Vdc resistive load, 250 Vac/3 A, 2 A, 30 Vdc inductive full load, 380 Vac/125 Vdc max. operating voltage

General specifications

PRODUCT NAME	Eaton General-purpose relay
CATALOG NUMBER	D4PR2T1
UPC	782114160671
PRODUCT LENGTH/DEPTH	1.14 in
PRODUCT HEIGHT	0.5 in
PRODUCT WIDTH	0.51 in
PRODUCT WEIGHT	0.04 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	cRUus UL Listed file E1491 UL Listed file E65657 CSA file No. LR701519
CATALOG NOTES	Indicator lamp available. Consult sales office or customer support center for additional coil voltages.
PRODUCT TYPE	General-purpose relay

Powering Business Worldwide

Product specifications

AMPERAGE RATING	5A
COVER	Plain
COIL VOLTAGE	24 Vdc
CONTACT CONFIGURATION	DPDT
INDUCTIVE FULL LOAD	2 A at 250 Vac, 3 A at 30 Vdc
QUANTITY	1
RESISTIVE LOAD	5 A, 240 Vac, 30 Vdc
SERIES	D4
VOLTAGE - MAX	380 Vac/125 Vdc

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - D4PR2T1

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.