Specifications



Photo is representative





Eaton MMX34AA014F0-0

Eaton M-Max Series Adjustable Frequency AC Drives Basic Controller, Full version, AA software design series, EMC filter, FS3 frame, 380-480V, 460V, IP20 enclosure rating, 10 hp, 14A output, 18.7A input, Three-phase in, three-phase out

General specifications	
PRODUCT NAME	Eaton M-Max Series sensorless vector adjustable frequency drive
CATALOG NUMBER	MMX34AA014F0-0
UPC	786685268866
PRODUCT LENGTH/DEPTH	3.94 in
PRODUCT HEIGHT	4.27 in
PRODUCT WIDTH	10.33 in
PRODUCT WEIGHT	2.18 lb
WARRANTY	2 year
COMPLIANCES	RoHS Compliant CE Marked EMC Category C2, C3, and C4 (Level H): With an internal RFI filter option C-Tick Compliant
CERTIFICATIONS	cUL Certified EN 61800-3 EN 61800-5-1 UL Listed EN 60204-1
CATALOG NOTES	Horsepower ratings are based on the use of a 240V, 460V, and 575V NEMA B, four- or six-pole squirrel cage induction motor and are for reference only.

Powering Business Worldwide

Product specifications

HORSEPOWER	10 hp
PHASE	Three-phase in, three-phase out
SPECIAL FEATURES	AA software design series, EMC filter
TYPE	Full version
VOLTAGE RATING	380-480 V, 460 V
FRAME SIZE	3
RATING	IP20
INPUT CURRENT	18.7 A
OUTPUT CURRENT - MAX	14 A

Resources

CATALOGS	Solid-State Motor Control, Variable Frequency Drives, Volume 6, Tab 2
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - MMX34AA014F0-0

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.