Specifications



Eaton XTOB150GC1

Eaton XT IEC bimetallic overload relay, 120-150A overload range, 90 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 80-170A contactor, 10A trip type

General specifications	
PRODUCT NAME	Eaton XT IEC bimetallic overload relay
CATALOG NUMBER	XTOB150GC1
EAN	4015082784669
PRODUCT LENGTH/DEPTH	3 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	3 in
PRODUCT WEIGHT	0.7 lb
COMPLIANCES	RoHS Compliant CE Marked ATEX Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
PRODUCT TYPE	Bimetallic overload relay

Powering Business Worldwide

Product specifications

OVERLOAD RANGE	120-150 A
FRAME SIZE	90 mm
MOUNTING	Direct

Resources

BROCHURES	C440 Electronic Overload Relay
CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
MULTIMEDIA	Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOB150GC1

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.