Specifications



Photo is representative

Eaton XTOB220LC1

Eaton XT IEC bimetallic overload relay, 160-220A overload range, 140 mm Frame size, 1NO-1NC contact configuration, used with 185-250A, 10A trip type

General specifications	
PRODUCT NAME	Eaton XT IEC bimetallic overload relay
CATALOG NUMBER	XTOB220LC1
EAN	4015082100742
PRODUCT LENGTH/DEPTH	5.67 in
PRODUCT HEIGHT	6.65 in
PRODUCT WIDTH	5.04 in
PRODUCT WEIGHT	3.5 lb
COMPLIANCES	ATEX Compliant CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Short-circuit Type 1 rating is 500A and short-circuit Type 2 rating is 400A for separate mounting. The main current parameters are defined by the main current wiring that is used.
PRODUCT TYPE	Bimetallic overload relay

Powering Business Worldwide

Product specifications

USED WITH	185-250A
OVERLOAD RANGE	160-220 A
TYPE	XT IEC Bimetallic Overload Relay
FRAME SIZE	140 mm
CONTACT CONFIGURATION	1 NO, 1 NC
TRIP TYPE	10 A

Resources

BROCHURES	C440 Electronic Overload Relay
CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
MULTIMEDIA	Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTOB220LC1

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.