Specifications



Photo is representative

Eaton DCU3061URM

Eaton heavy duty DC disconnect,DC disconnect/ungrounded system,30A,NEMA 3R,Painted galvanized steel,Non-fusible,Ungrounded,#14-#2 AWG lug capacity, #14-1/0 AWG solid return,600 Vdc,3,DC Photovoltaic Applications

General specifications	
PRODUCT NAME	Eaton heavy duty DC disconnect
CATALOG NUMBER	DCU3061URM
UPC	786685557427
PRODUCT LENGTH/DEPTH	25.5 in
PRODUCT HEIGHT	9 in
PRODUCT WIDTH	13.25 in
PRODUCT WEIGHT	40 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
CERTIFICATIONS	NEC 690 per UL 1741 UL 98B
CATALOG NOTES	Not all configurations for ampere rating and number of circuits are available. All circuit configurations can be found in the product dimension tables.

Powering Business Worldwide

Product specifications

TYPE	DC disconnect/ungrounded system
AMPERAGE RATING	30A
NUMBER OF CIRCUITS	3
GROUND	Ungrounded
MAXIMUM VOLTAGE	600 VDC
NEMA RATING	NEMA 3R
PROTECTION	Non-fusible
APPLICATION	Solar
MAIN LUG WIRE SIZE	#14-#2 AWG lug capacity, #14-1/0 AWG solid return
SYSTEM VOLTAGE	600 VDC per pole
VOLTAGE RATING	600 VDC
SERIES	DC Photovoltaic Applications
ENCLOSURE	NEMA 3R
ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CONFIGURATION	Non-fusible
SWITCH TYPE	Heavy duty
PROTECTION	Non-fusible

Resources

MULTIMEDIA	Switching Devices Flex Center Double Up on Safety
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DCU3061URM

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.