Specifications

Photo is representative

Eaton DM1-32017EB-S20S

Eaton PowerXL DM1 micro variable frequency drive, Three-phase, 230 V, 17 A, Internal EMC filter, Internal brake chopper, Multi segment LCD display, IP20, ST0 SIL2 and ethernet I/P, Modbus TCP onboard

General specifications

PRODUCT NAME	Eaton PowerXL DM1 micro variable frequency drive
CATALOG NUMBER	DM1-32017EB-S20S
UPC	786689351021
PRODUCT LENGTH/DEPTH	7.09 in
PRODUCT HEIGHT	8.66 in
PRODUCT WIDTH	4.29 in
PRODUCT WEIGHT	5.8 lb
CERTIFICATIONS	UL Listed

Powering Business Worldwide

Product specifications

BRAKE CHOPPER	Internal brake chopper
SERIES	DM1
DRIVE TYPE	General purpose
FRAME SIZE	FR2
ENCLOSURE RATING	IP00
INPUT PHASES	Three-phase
OUTPUT PHASES	Three-phase
ELECTROMAGNETIC COMPATIBILITY FILTER	Yes
INTERNAL CHOKE	No
INTERNAL LINE REACTOR	No
AMBIENT OPERATING TEMPERATURE RANGE	• -10 to 50 °C CT • -10 to 40 °C VT
CONFORMAL COATED BOARDS	Yes
USER INTERFACE	Multi-segment
INPUT VOLTAGE RANGE	200-240 Vac
INPUT FREQUENCY RANGE	50-60 Hz
OUTPUT FREQUENCY RANGE	0-400 Hz
MAX OVERLOAD	200 %
FUSE SIZE - MAX	60
MOUNTING TYPE	DIN rail Panel mount
DIGITAL INPUTS	4
ANALOG INPUTS	1
RELAY OUTPUTS	2
DIGITAL OUTPUTS	0
HIGH OVERLOAD (CT) HP	5
HIGH OVERLOAD (CT) KW	4
LOW OVERLOAD (VT) KW	5.5
LOW OVERLOAD (VT) AMPS	25
HIGH OVERLOAD (CT) AMPS	17
LOW OVERLOAD (VT) HP	7.5
COMMUNICATIONS ONBOARD	Modbus RTU Modbus TCP Ethernet/IP BACnet IP BACnet MS/TP

Resources

SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DM1-32017EB-S20S

	Bluetooth
COMMUNICATIONS OPTIONAL	CANopen PROFIBUS SmartWireDT
MOTOR CONTROL MODES	V/Hz Open loop vector control
MOTOR TYPE	Induction Induction motor Permanent magnet motor (SPM/IPM)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.