Specifications







Eaton 9SX1500

Eaton 9SX online, extended runtime UPS, 1500 VA, 1350 W, 5-15P input, Outputs: (6) 5-15R, 9.9"Hx6.3"Wx17.1"D, 41.9 lb., network card optional

General specifications	
PRODUCT NAME	Eaton 9SX UPS
CATALOG NUMBER	9SX1500
UPC	743172091246
PRODUCT LENGTH/DEPTH	17.1 in
PRODUCT HEIGHT	9.9 in
PRODUCT WIDTH	6.3 in
PRODUCT WEIGHT	41.9 lb
WARRANTY	3 year limited
COMPLIANCES	FCC Compliant CE Marked
CERTIFICATIONS	cULus Listed ICC-ES AC156 OSHPD Seismic certified
GLOBAL CATALOG	9SX1500

Powering Business Worldwide

Battery

BATTERY MANAGEMENT	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
EXTENDED BATTERY CAPABILITY	Yes

Electrical input

INPUT CONNECTION	5-15P
INPUT CORD LENGTH	8 ft
INPUT NOMINAL VOLTAGE	120V default (100/110/120/125V)
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
INPUT POWER FACTOR	>.99

Electrical output

RECEPTACLE	(6) 5-15R
TOPOLOGY	Online/Double-conversion
WATTAGE	1350 W
VA RATING	1500 VA
OUTPUT WAVEFORM	True sine wave
VOLTAGE	120V
OUTPUT POWER FACTOR	0.9
OUTPUT NOMINAL VOLTAGE	120V default (100/110/120/125V)
OUTPUT FREQUENCY	50/60 Hz
FEED TYPE	1

Communications

COMMUNICATION	• (1) MiniSlot • (1) USB port • (1) Serial RS-232 port • (1) RPO/ROO/Signal input terminal • (1) mini-terminal block for output relay
EXPANSION SLOTS	• (1) Mini-Slot (MS) expansion port. Optional connectivity cards may be ordered separately. • - Gigabit Web/SNMP card part number: NETWORK-M3 • - Modbus card part number: INDGW-M2 • - Relay card part number: RELAY-MS
USER INTERFACE	5-button graphical user interface
POTENTIAL FREE SWITCH CONTACT	Yes

Environmental

ALTITUDE	3000 m
BTU RATING	Online : 543 BTU/hr, Battery : 658 BTU/hr, High efficiency : 220 BTU/hr
NOISE LEVEL	51 dB at 1m
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

Additional specifications

SPECIAL FEATURES	This product is designed with features typically required in commercial applications, including network connectivity and a metal case
FORM FACTOR	Tower
CONSTRUCTION TYPE	Free standing model
EFFICIENCY AT MAX. LOAD	90.44%
PACKAGE CONTENTS	• 9SX 1500 VA UPS • Quick start guide • RS-232 serial cable • USB cable
INTERNAL BYPASS	Yes

Warranty and support

STANDARD FACTORY WARRANTY	• 3-YEAR FACTORY WARRANTY • - 3 years • - Parts, electronics and batteries coverage • - Standard ground shipping • - Technical support
EXTENDED SERVICE PLANS	• ADVANCED DEPOT EXCHANGE • - 5-year depot repair: 9SW5Y-1500UC • - Expedited parts coverage for 5 years • - Parts, electronics and UPS batteries coverage • - Next business day shipping • - Technical support • • 5-YEAR ON-SITE PLAN: WFLN75XX-2509UC • - On-site parts and labor coverage for years 5 • - Parts, electronics and UPS batteries coverage • - 24x7 on-site labor coverage, next-day response • - Next-day shipping • - Technical support

Resources

BROCHURES	Quick start guide for Eaton 9SX UPS 120V models Eaton 9SX UPS brochure Eaton 9SX UPS installation and user manual Eaton 9SX UPS technical specifications Eaton 9SX UPS visio stencils
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 9SX1500

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.