Specifications



Photo is representative

Eaton RM25030-1CHR

Eaton Bussmann Series RM modular fuse block, Box lugs with hex screws, 30 A, 1P, 120°C, 50 lb-in max, Class R, CVR(I)-RH-25030, Black, 200 kAIC, 75 °C, Stranded, DIN rail, Panel, 250 V, #2-14 AWG

General specifications	
PRODUCT NAME	Eaton Bussmann Series RM modular fuse block
CATALOG NUMBER	RM25030-1CHR
UPC	051712682893
PRODUCT LENGTH/DEPTH	3.2 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	1 in
PRODUCT WEIGHT	0.1128125 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	ARO European Pressure Equipment Directive (PED) 97 /23 EC

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	30 A
IMPULSE WITHSTAND VOLTAGE	200 kA RMS symmetrical
INTERRUPT RATING	200 kAIC
SHORT-CIRCUIT RATING	200 kA RMS symmetrical
TORQUE RATING	50 lb-in maximum
VOLTAGE RATING	250 V

Physical details

COLOR	Black
CONDUCTOR MATERIAL RATED FOR	Both
CONDUCTOR TEMPERATURE RATING	75 °C
CONDUCTOR TYPE	Stranded
FUSE TYPE	Class R
NUMBER OF POLES	Single-pole
OPERATING TEMPERATURE - MAX	120 °C
OPERATING TEMPERATURE - MIN	120 °C
WIRE SIZE	#2-14 AWG

General information

ACCESSORIES	CVR(I)-RH-25030
CONNECTION	Box lug
MOUNTING METHOD	DIN rail Panel
SPECIAL FEATURES	Box Lugs with Hex Screws

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 RM25030-1CHR~FUSE BLK R250V 30A 1P HX
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2202
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RM25030-1CHR

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.