Specifications



Photo is representative

Eaton RM25060-2CHR

Eaton Bussmann Series RM modular fuse block, Box lugs with hex screws, 60 A, 2P, 120°C, 50 lb-inches max, Class R, CVR(I)-RH-25060, Black, 200 kAIC, 75 °C, Stranded, DIN rail, Panel, 250 V, #2-14 AWG

General specifications	
PRODUCT NAME	Eaton Bussmann Series RM modular fuse block
CATALOG NUMBER	RM25060-2CHR
UPC	051712620840
PRODUCT LENGTH/DEPTH	2.7 in
PRODUCT HEIGHT	4.2 in
PRODUCT WIDTH	2.7 in
PRODUCT WEIGHT	0.38 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	ARO European Pressure Equipment Directive (PED) 97 /23 EC

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	60 A
IMPULSE WITHSTAND VOLTAGE	200 kA RMS symmetrical
INTERRUPT RATING	200 kAIC
SHORT-CIRCUIT RATING	200 kA RMS symmetrical
TORQUE RATING	50 lb-in maximum
VOLTAGE RATING	250 V

Physical details

COLOR	Black
CONDUCTOR MATERIAL RATED FOR	Both
CONDUCTOR TEMPERATURE RATING	75 °C
CONDUCTOR TYPE	Stranded
FUSE TYPE	Class R
NUMBER OF POLES	Two-pole
OPERATING TEMPERATURE - MAX	120 °C
OPERATING TEMPERATURE - MIN	120 °C
WIRE SIZE	#2-14 AWG

General information

ACCESSORIES	CVR(I)-RH-25060
CONNECTION	Box lug
MOUNTING METHOD	DIN rail Panel
SPECIAL FEATURES	Box Lugs with Hex Screws

Resources

CATALOGS	RM25060-2CHR~FUSE BLK, R 250V 60A 2P Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2202
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - RM25060-2CHR

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights Reserved.