Specifications







Eaton HM60060-3MW14

Eaton Bussmann series HM power distribution fuse block, Multi-wire load-side lug, 60 A, 3P, 120°C, Class H, Class K, CVR(I)-RH-60060, Black, Box lug, 10 kA, 75 °C, Stranded, DIN rail, Panel, 600 V

General specifications

PRODUCT NAME	Eaton Bussmann series HM power distribution fuse block
CATALOG NUMBER	HM60060-3MW14
UPC	051712620468
PRODUCT LENGTH/DEPTH	6.8 in
PRODUCT HEIGHT	2.6 in
PRODUCT WIDTH	4.6 in
PRODUCT WEIGHT	0.78375 lb
WARRANTY	Not Applicable
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	ARO European Pressure Equipment Directive (PED) 97 /23 EC

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	60 A
IMPULSE WITHSTAND VOLTAGE	10 kA RMS symmetrical
INTERRUPT RATING	10 kAIC
SHORT-CIRCUIT RATING	10 kA RMS symmetrical
TORQUE RATING	50 lb-in maximum
VOLTAGE RATING	600 V

Physical details

COLOR	Black
CONDUCTOR MATERIAL RATED FOR	Both
CONDUCTOR TYPE	Stranded
FUSE TYPE	Class H Class K
NUMBER OF POLES	Three-pole
OPERATING TEMPERATURE - MAX	120 °C
OPERATING TEMPERATURE - MIN	120 °C

General information

ACCESSORIES	CVR(I)-RH-60060
CONNECTION	Box lug
MOUNTING METHOD	DIN rail Panel
SPECIAL FEATURES	Multi-Wire Load-Side Lug

Resources

CATALOGS	Bussmann series complete full line catalog no. 1007 HM60060-3MW14~FUSE BLK, H 600V 60A 3P
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2204
MULTIMEDIA	Bussmann series Fuseology Class H(K), J and R Power distribution fuse block overview
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - HM60060-3MW14

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights Reserved.