Specifications



Photo is representative





Eaton XTCR012B21T

Eaton XT IEC contactor, 12A, 24 Vac, 50-60 Hz, 2NO-2NO, 12A, Frame B, 45 mm, 50-60 Hz, 0.5, 2/ 3, 3, 10, 10 hp (1/3PH @115, 230/200, 230, 460, 575 V), Three-pole, Reversing, , Screw terminals, Full voltage reversing contactor

General specifications	
PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCR012B21T
UPC	782116885084
PRODUCT LENGTH/DEPTH	5.25 in
PRODUCT HEIGHT	5 in
PRODUCT WIDTH	5.75 in
PRODUCT WEIGHT	1.5 lb
WARRANTY	1 year
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	CSA Certified IEC 60947 EN 60947 UL Listed
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)
PRODUCT TYPE	Contactors

Powering Business Worldwide

Product specifications

AMPERAGE RATING	12A
HP RATING - MAX	0.5, 2/ 3, 3, 10, 10 hp (1/3PH @115,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage reversing contactor
FREQUENCY RATING	50-60 Hz
FRAME SIZE	45 mm
TERMINALS	Screw terminals
COIL	24 Vac, 50/60 Hz
COIL VOLTAGE	24 Vac, 50-60 Hz
CONTACT CONFIGURATION	2 NO, 2 NO
CONTINUOUS AMPERE RATING	12 A
SERIES	XT IEC
OPERATION	Reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCR012B21T

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.