Powering Business Worldwide

pe.eaton.com

Ferrule style high speed fuse links



FWC-32A10F

UPC:051712796484

Dimensions:

- **Height:** 23 MM
- **Length:** 38 MM
- **Width:** 11 MM

Weight:.006 KG

Warranties:

- Not Applicable

Specifications:

- **Type:** FWC, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Amperage Rating:** 32A
- **Voltage Rating:** 600 Vac (UL)
- **Interrupt Rating:** 200kA ac RMS Symmetrical, 50kA at 300 Vdc
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Used With:** Finger safe holders/blocks and striker
- **Pre Arc (I2T):** 95
- **Clearing (I2T):** Clearing at Rated voltage: 600
- **Diameter:** 10 MM
- **Material:** Ceramic
- **Color:** White
- **Class:** Class aR
- **Connection:** Ferrule end X ferrule end
- **Watt Losses:** 7.5W
- **Mounting:** Fuse holder and blocks
- **Quantity:** 10
- **Fuse Size:** 10 X 38 mm

Supporting documents:

- 32AMP 600V AC FERRULE 10 X 38MM

Certifications:

- CSA Certified
- UL Recognized

Product compliance:

- CE Marked

© 2016 Eaton. All rights reserved.