Powering Business Worldwide

pe.eaton.com



Time-Delay Fuse

TR2/C515-1.5-R

UPC:051712650915

Dimensions:

- **Height:** .217 IN
- **Length:** .598 IN
- **Width:** .217 IN

Weight:.001 LB

Warranties:

- Not Applicable

Specifications:

- **Type:** Electronic
- **Application:** Electronic circuits, printed circuit boards
- **Amperage Rating:** 1.5A
- **Voltage Rating:** 250 Vac
- **Interrupt Rating:** 100A at 250 Vac, 10000A at 125 Vac
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Used With:** Tin coated axial leads
- **Response Time:** 60 min maximum at 135%, 3 s minimum at 135%, 120 s minimum at 200%
- **Voltage Drop:** Maximum: 240 mV
- **Melting (L2T):** Typical: 31.989 I2t
- **Diameter:** 5.2 MM
- **Material:** Glass tube, nickel-plated brass endcap
- **Connection:** Ferrule end X ferrule end
- **Quantity:** 1500 fuses packed into tape on a reel (20.3mm lead wire length)
- **Resistance:** Typical: .1 ohms

Supporting documents: No Data

Certifications: No Data

Product compliance:

- EIA-IS-730
- RoHS Compliant

© 2016 Eaton. All rights reserved.