

Product data sheet

Specifications



plug-in solid state relay- 12.5 mm - input - 24 V DC type 2

ABS7EC3B2

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Advantys Telefast ABE7
Product or Component Type	Plug-in solid state relay
Relay Type	Input relay
minimum ordered quantity	Set of 4

Complementary

Response time	<= 0.05 ms from state 0 to 1 <= 0.4 ms from state 1 to 0
Width pitch dimension	0.5 in (12 mm)
Product Compatibility	ABE7P16F310 ABE7P16F310E ABE7P16F312
Discrete input voltage	24 V DC, type 2
Discrete output voltage	5...24 V DC
Product Weight	0.031 lb(US) (0.014 kg)

Ordering and shipping details

Category	US10CP222375
Discount Schedule	0CP2
GTIN	3389110720808
Returnability	Yes
Country of origin	LV

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.709 in (1.800 cm)
Package 1 Width	1.260 in (3.200 cm)
Package 1 Length	1.772 in (4.500 cm)
Package weight(Lbs)	0.317 oz (9.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	1.969 in (5.000 cm)
Package 2 Width	1.969 in (5.000 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Length	2.559 in (6.500 cm)
Package 2 Weight	1.623 oz (46.000 g)
Unit Type of Package 3	S02
Number of Units in Package 3	128
Package 3 Height	5.906 in (15.000 cm)
Package 3 Width	11.811 in (30.000 cm)
Package 3 Length	15.748 in (40.000 cm)
Package 3 Weight	4.074 lb(US) (1.848 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

California proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

PVC free

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Circularity Profile

No need of specific recycling operations

Take-back

No

WEEE Label

 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Connections and Schema

Internal Wiring Diagram




Image of product / Alternate images

Alternative

