Product data sheet

Specifications



plug-in solid state relay - 12.5 mm - output - 24 V DC - 2 A

ABS7SC3BA

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	Advantys Telefast ABE7
Product or Component Type	Plug-in solid state relay
Relay Type	Output relay
minimum ordered quantity	Set of 4

Complementary

Response time	<= 0.1 ms from state 1 to 0 <= 0.2 ms from state 0 to 1
Width pitch dimension	0.5 in (12 mm)
Product Compatibility	ABE7P16T318 ABE7P16T330 ABE7R16T330 ABE7P16T334 ABE7P16T318E ABE7P16T330E ABE7R16T332
Discrete input voltage	24 V DC
Discrete output voltage	24 V DC self-protected
Discrete output current	2000 mA
Current state 0 guaranteed	0.4 mA DC
Current state 1 guaranteed	2.9 mA DC
Voltage state 0 guaranteed	3.8 V DC
Voltage state 1 guaranteed	18.6 V DC
Product Weight	0.035 lb(US) (0.016 kg)

Ordering and shipping details

Category	US10CP222375
Discount Schedule	0CP2
GTIN	3389110720761
Returnability	Yes
Country of origin	LV

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.260 in (3.200 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	0.394 in (1.000 cm)
Package 1 Length	1.772 in (4.500 cm)
Package weight(Lbs)	0.388 oz (11.000 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	2.756 in (7.000 cm)
Package 2 Width	3.150 in (8.000 cm)
Package 2 Length	3.937 in (10.000 cm)
Package 2 Weight	2.469 oz (70.000 g)
Unit Type of Package 3	S02
Number of Units in Package 3	128
Package 3 Height	5.906 in (15.000 cm)
Package 3 Width	11.811 in (30.000 cm)
Package 3 Length	15.748 in (40.000 cm)
Package 3 Weight	4.707 lb(US) (2.135 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Connections and Schema

Internal Wiring Diagram




Image of product / Alternate images

Alternative

