

Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

SM956A420000

Telemecanique Sensors
1875 Founders Drive
Dayton, OH 45420-4017
Customer Care Center : 1-800-435-2121
Web : www.tesensors.com

Technical Information:

Sensing Window:	
Far Limit:	
Sensing Range:	120.0 mm to 2.0 m (4.7 in to 79.0 in)
Circuit Type:	
Output Mode:	Inverse 4 to 20 mA
Volts Type:	DC
Voltage Range:	15-24 VDC
Max Load:	10 - 500 ohm
Current Consumption:	80 mA
Sonic Frequency:	200 Hz
Temp Range:	0° to 50° C (32° to 122° F)
NEMA Type:	4X (indoor use only)
IP Rating:	IP67
Standards:	UL, CE Rohs

Specification:

Sensor Type:	Ultrasonic Sensor
Description:	Ultrasonic Sensor, Analog - Current (mA), 30 mm Barrel, 15-24 VDC
Body Style:	Barrel
Diameter:	mm
Housing Material:	
Face Material:	Silicone Rubber
Field Configurable:	No
Functionality:	Standard: No Foreground Or Background Suppression
Cable Size:	
Connector Type:	M12
Special Features:	