Product data sheet

Specifications



Lifting eyebolts, PanelSeT SFN, Spacial SF, steel , M12 , set of 4

NSYSFEB

Product availability: Stock - Normally stocked in distribution facility

Main

Area	PanelSeT
category	Lifting accessory
Product or Component Type	Lifting eye
Application	Multi-purpose
Mounting Location	Enclosure top
Mounting Support	Directly in the axis of the uprights
Range compatibility	Prisma Prisma PH PanelSeT PanelSeT SFHD PanelSeT PanelSeT SFM
Device composition	4 eyebolt
Quantity per Set	Set of 1

Complementary

Material	cast steel
Surface Finish	Galvanized
Fixing mode	Screwed
Permanent permissible load	749.6 lb(US) (340 kg) for 1 eyebolt vertical direction
Height	2.5 in (62.5 mm)
Width	2.2 in (55 mm)
Depth	0.9 in (24 mm)
Diameter	1.1 in (29 mm)
ISO thread	M12

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606485131542
Returnability	Yes
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Height	2.953 in (7.500 cm)
Package 1 Width	3.543 in (9.000 cm)
Package 1 Length	5.512 in (14.000 cm)
Package weight(Lbs)	24.409 oz (692.000 g)
Unit Type of Package 2	P12
Number of Units in Package 2	400
Package 2 Height	31.496 in (80.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	638.900 lb(US) (289.800 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**5 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**3 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.2 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**2 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
PVC free	**Yes**
Silicon free	**No**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**98**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**