Product data sheet

Specifications



Standard shunt trip release MX, ComPacT NSXm, 48VDC, 48VAC 50/60Hz

LV426842

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	ComPact
Range of Product	ComPacT NSXm
Device short name	MX
Product or Component Type	Voltage release
Device Application	Control
Voltage release type	Opening coil Shunt trip release
Control Type	Standard
[Uc] control circuit voltage	48 V AC 50/60 Hz 48 V DC
Range compatibility	ComPact ComPacT NSXm ComPact ComPact NSXm PowerPact PowerPact B

Complementary

Operating threshold	0.7 Un opening
Response time	< 50 ms
Control signal type	Maintained Impulse
Impulse duration	>= 20 ms
Auxiliary connection terminal	spring

Ordering and shipping details

Category	US10DE201136
Discount Schedule	0DE2
GTIN	3606485413051
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.4 in (3.5 cm)
Package 1 Width	2.4 in (6 cm)
Package 1 Length	3.1 in (8 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package weight(Lbs)	2.3 oz (64 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.5 in (9 cm)
Package 2 Width	5.1 in (13 cm)
Package 2 Length	7.3 in (18.5 cm)
Package 2 Weight	24.3 oz (690 g)
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	11.8 in (30 cm)
Package 3 Width	11.8 in (30 cm)
Package 3 Length	15.7 in (40 cm)
Package 3 Weight	19.2 lb(US) (8.7 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	2
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	75582d60-9779-4641-a03b-18e996230a58
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
Silicon free	No

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.