Product data sheet

Specifications



Folding support tray - 600 mm enclosure - 30 kg load

NSYSDT6

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	PanelSeT
Product or Component Type	Folding support tray
Application	Door accessories
Nominal dimensions of the housing	- W: 23.6 in (600 mm)
Mounting Location	Door cross rail On door reinforcement frame
Mounting Support	Direct mounting
Range compatibility	PanelSeT SF, SM, SFX and SMX enclosures
Device composition	1 x fixing element 1 x folding support tray
Quantity per Set	Set of 1

Complementary

Material	Door steel
color	Door Gray RAL 7035)
Surface Finish	Painted
Fixing mode	Direct fixing - door
Adjustment	Adjustable in height, steps of 25 mm door
Operating angle	45 ° 60 ° 75 ° 90 °
Maximum load	30 kg
Height	2.0 in (50 mm)
Width	Nominal: 12.8 in (325 mm)
Depth	13.8 in (350 mm)
thickness	0.06 in (1.5 mm)

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1
GTIN	3606485131504
Returnability	No
Country of origin	ES

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	1.969 in (5.000 cm)
Package 1 Width	14.567 in (37.000 cm)
Package 1 Length	18.110 in (46.000 cm)
Package weight(Lbs)	7.544 lb(US) (3.422 kg)
Unit Type of Package 2	PAM
Number of Units in Package 2	80
Package 2 Height	24.803 in (63.000 cm)
Package 2 Width	39.370 in (100.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	625.584 lb(US) (283.760 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**11 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**7 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.3 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.3 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**4 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**52da316e-d4e1-4114-85c0-32a03b2934fd**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
PVC free	**Yes**
Silicon free	**No**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**98**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**