# *Product datasheet*
## *Characteristics*

# SM952A410000LE



## Main

| | |
|---|---|
| Range of product | Hyde Park |
| Sensor type | Ultrasonic sensor |
| Series name | Superprox 900 |
| Device short name | SM952 |
| Sensor design | Cylindrical M30 |
| [Sn] nominal sensing distance | 6.56 ft (2 m) |
| Type of sensing window | Adjustable |
| Material | Plastic |
| Enclosure material | ULTEM |
| Front material | Silicone rubber |
| Type of output signal | Discrete |
| Discrete output function | 1 NO |
| ISO thread | M30 x 1.5 |
| Wiring technique | 4-wire |
| [Us] rated supply voltage | 12...24 V DC (overload and short-circuit protection) |
| Supply voltage limits | 10...28 V DC |
| Discrete output type | PNP/NPN |
| Electrical connection | 1 male connector M12 4 pins |
| Product specific application | Dual-level - pump-in latch |

## Complementary

| | |
|---|---|
| [Sd] sensing range | 0.39...6.56 ft (0.12...2 m) |
| Maximum differential travel | 0.1 in (2.5 mm) |
| Blind zone | 4.72 in (120 mm) |
| Transmission frequency | 200 kHz |
| Repeat accuracy | 0.87 % |
| Beam angle | 10 ° |
| Minimum size of detected object | Cylinder diameter 1.6 mm - up to 305 mm sensing distance |
| Current consumption | 100 mA |
| Maximum switching current | 100 mA (reverse polarity protection) |
| Height | 1.18 in (30 mm) |
| Width | 1.37 in (34.7 mm) |
| Depth | 1.18 in (30 mm) |
| Length | 3.78 in (96 mm) |
| Product weight | 0.57 lb(US) (0.26 kg) |

## Environment

| | |
|---|---|
| product certifications | UL |
| marking | CE |
| NEMA degree of protection | NEMA 4X (indoor use only) |
| IP degree of protection | IP67 |
| ambient air temperature for operation | 32...122 °F (0...50 °C) |
| ambient air temperature for storage | -4...176 °F (-20...80 °C) |
| relative humidity | 100 % without condensation |
| vibration resistance | +/-1 mm conforming to IEC 60068-2-6 10...55 Hz |
| shock resistance | 30 gn in all 3 axes 11 ms conforming to IEC 60068-2-27 |
| resistance to electromagnetic fields | 9.14 V/yd (10 V/m) (level 3) conforming to IEC 61000-4-3 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---|---|
| resistance to fast transients | 1 kV (level 3) conforming to IEC 61000-4-4 |

## Contractual warranty

| | |
|---|---|
| Warranty period | 18 months |