

Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

SC956A8C0

Telemecanique Sensors

Telemecanique Sensors
1875 Founders Drive
Dayton, OH 45420-4017
Customer Care Center : 1-800-435-2121
Web : www.tesensors.com

Technical Information:

Sensing Window:	
Far Limit:	
Sensing Range:	203.0 mm to 8.0 m (8.0 in to 26.0 ft)
Circuit Type:	
Output Mode:	Current
Volts Type:	DC
Voltage Range:	15-24 VDC
Max Load:	10 - 500 ohm
Current Consumption:	80 mA
Sonic Frequency:	75 Hz
Temp Range:	-20° to 60° C (-4° to 140° F)
NEMA Type:	4X (indoor use only)
IP Rating:	IP67
Standards:	UL, CE Rohs

Specification:

Sensor Type:	Ultrasonic Sensor
Description:	Ultrasonic Sensor, Analog - Current (mA), 30 mm Barrel, 15-24 VDC
Body Style:	Barrel
Diameter:	mm
Housing Material:	
Face Material:	Glass Epoxy
Field Configurable:	Yes, using AC441 Configurator and Superprox+ Software
Functionality:	Configurable
Cable Size:	
Connector Type:	M12
Special Features:	