Product datasheet
Characteristics

QO142M200PCMR



Main

Product or component type	Load Center
Range of product	QO
Load center type	Main breaker
Line Rated Current	200 A
Number of spaces	42
Short-circuit current	22 kA
Number of circuits	42
Number of tandem circuit breakers	0
Phase	1 phase
System Voltage	120/240 V AC

Complementary

Bus rated current	225 A
AWG gauge	AWG 4...300 kcmil (copper or aluminium)
Number of circuits	6 standard 18 maximum
NEMA degree of protection	NEMA 1 indoor
Mounting mode	Flush-mounted Surface mounted
Cover type	Combination flush/surface cover
Electrical connection	Feed-thru lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Surface finish	Baked enamel white
Provided equipment	Circuit breaker 1 2P 200 A 120/240 V AC main supply ready assembled
Product compatibility	Solar ready Electric vehicle ready
Product certifications	UL listed

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1742 - Schneider Electric declaration of conformity	Compliant - since 1742 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.