

Product data sheet

Specifications



Plain door, PanelSeT SFN, PanelSeT SM, for electrical enclosure H2000 W1000mm

NSYSFND2010

Product availability: Stock - Normally stocked in distribution facility

Main

Range	PanelSeT
Accessory / separate part category	Enclosure accessory
Product or Component Type	Door
Application	Multi-purpose
For enclosure nominal dimensions	- H: 78.7 in (2000 mm) W: 39.4 in (1000 mm)
Mounting Location	Front
Range compatibility	PanelSeT SFN
Device composition	1 door 1 lock with handle and 5 mm double bar insert 1 locking bar system 4 points 1 reinforcement frame 4 hinges 4 locking bar catches
Quantity per Set	Set of 1

Complementary

Material	sheet steel
color	Gray RAL 7035)
Surface Finish	Epoxy-polyester powder
Lock type	Lock 5 mm double bar
Number of locks	1
Door type	External plain
Door opening side	Reversible 120 °)
Maximum load	60 kg/m²
Height	Nominal: 77.4 in (1966 mm)
Width	Nominal: 38.1 in (969 mm)
Product Weight	38.6 lb(US) (17.5 kg)

Environment

IK degree of protection	IK10
-------------------------	------

Ordering and shipping details

Category	US10ES180036
Discount Schedule	0ES1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

GTIN	3606486378144
Returnability	Yes
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.165 in (5.500 cm)
Package 1 Width	38.976 in (99.000 cm)
Package 1 Length	78.740 in (200.000 cm)
Package weight(Lbs)	82.673 lb(US) (37.500 kg)
Unit Type of Package 2	P2M
Number of Units in Package 2	16
Package 2 Height	39.961 in (101.500 cm)
Package 2 Width	47.244 in (120.000 cm)
Package 2 Length	78.740 in (200.000 cm)
Package 2 Weight	1408.755 lb(US) (639.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	191 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	93 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	10 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	82 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	695ecfbd-bb51-4da6-80d3-6b38e7bcfee6
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	97
Circularity Profile	End of Life Information
Take-back	No

Technical Illustration

Dimensions



Technical Illustration

Exploded view



Technical illustration

Product Installation



Technical illustration

Product Installation

