# Product data sheet

Specifications




## CONTROL STATION 600VAC 5A T-B OPEN-CLOSE

9001BG207

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Harmony 9001B |
| **Product or Component Type** | Complete control station |
| **Device short name** | 9001BG |

## Complementary

| | |
|---|---|
| **AC control voltage 50 HZ** | 125…600 V |
| **AC control voltage 60 HZ** | 125…600 V |
| **DC control voltage** | 125…600 V |
| **Control station composition** | 2 push-buttons OPEN-CLOSE |
| **Contacts type and composition** | 2 NO |
| **Number of command positions** | 2 |
| **Number of indicator lights** | 0 |
| **Connections - terminals** | Screw clamp terminal |
| **Number of push buttons** | 2 |
| **[Ie] rated operational current** | 5 A 600 V |
| **Number of selector switches** | 0 |
| **Number of key switches** | 0 |
| **Device mounting** | Surface |
| **Type of Installation** | Indoor |
| **Number of mushroom-shaped push-buttons** | 0 |
| **Emergency Power Off (EPO)** | No |
| **Number of contacts as normally closed contact** | 0 |
| **Number of contacts as normally open contact** | 2 |
| **Number of contacts as change-over contact** | 0 |
| **Housing material** | Metal |
| **Housing Colour** | Grey |
| **colour of cover** | Grey |

## Environment

| | |
|---|---|
| **NEMA degree of protection** | NEMA 1 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Product Certifications** | CSA LR25490 class 3211 03<br>CE<br>UL listed file E42259 CCN NKCR |
| **Environmental characteristic** | Standard environment |
| **NEMA Degree of Protection** | NEMA 13 |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CS121421 |
| **Discount Schedule** | 0CS1 |
| **GTIN** | 785901856665 |
| **Returnability** | Yes |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 2.200 in (5.588 cm) |
| **Package 1 Width** | 2.500 in (6.350 cm) |
| **Package 1 Length** | 3.800 in (9.652 cm) |
| **Package weight(Lbs)** | 9.440 oz (267.619 g) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant |
| REACh Regulation | Free of Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | No |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Take-back | No |

Dimensions Drawings

**Approximate Dimensions**

