Product data sheet

Specifications



Power cable SH3/MH3 motor to Lexium 52/62 drive, 1,5mm2, M23, 15m

VW3E1143R150

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	PacDrive 3
Product or Component Type	Power cable

Complementary

Range Compatibility	Lexium 62 Lexium 52 Lexium STS
Product compatibility	LXM 62 servo drive LXM 52 servo drive SH3055.P... SH3070.P/M... SH3100.P/M... SH31401M... MH3070.P... MH3100.P...
Connector type	M23
Material	Metal
Accessory / separate part destination	Holding brake Power supply Temperature sensor
Cable cross section	0.002 in² (1.5 mm²)
Cable length	49.2 ft (15 m)
Product Weight	8.459 lb(US) (3.837 kg)
Accessory / separate part category	Connection accessories

Ordering and shipping details

Category	US1PC5218353
Discount Schedule	PC52
GTIN	3606485287324
Returnability	No
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.953 in (7.500 cm)
Package 1 Width	13.386 in (34.000 cm)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	13.386 in (34.000 cm)
Package weight(Lbs)	7.981 lb(US) (3.620 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	3
Package 2 Height	11.8 in (30 cm)
Package 2 Width	15.7 in (40 cm)
Package 2 Length	23.6 in (60 cm)
Package 2 Weight	25.62 lb(US) (11.62 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**31 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**23 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.5 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**7 kg CO2 eq.**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**21**
Circularity Profile	**End of Life Information**
Take-back	**No**