Product data sheet
Characteristics

VY1F32AB1001
removable motor power terminal block



Main

Range of Product	Altivar
Accessory / separate part type	Connection terminal block
Accessory / separate part categor	Replacement part

Complementary

Range Compatibility	Altivar 32 Altivar Machine ATV320
Product compatibility	Variable speed drive ATV32 0.18 kW, 200...240 V, single phase Variable speed drive ATV32 0.37 kW, 200...240 V, single phase Variable speed drive ATV32 0.55 kW, 200...240 V, single phase Variable speed drive ATV32 0.75 kW, 200...240 V, single phase Variable speed drive ATV32 1.1 kW, 200...240 V, single phase Variable speed drive ATV32 1.5 kW, 200...240 V, single phase Variable speed drive ATV32 2.2 kW, 200...240 V, single phase Variable speed drive ATV32 0.37 kW, 380...500 V, three phase Variable speed drive ATV32 0.55 kW, 380...500 V, three phase Variable speed drive ATV32 0.75 kW, 380...500 V, three phase Variable speed drive ATV32 1.1 kW, 380...500 V, three phase Variable speed drive ATV32 1.5 kW, 380...500 V, three phase Variable speed drive ATV32 2.2 kW, 380...500 V, three phase Variable speed drive ATV32 3 kW, 380...500 V, three phase Variable speed drive ATV32 4 kW, 380...500 V, three phase Variable speed drive ATV320...B 0.18 kW, 200...240 V, single phase Variable speed drive ATV320...B 0.37 kW, 200...240 V, single phase Variable speed drive ATV320...B 0.55 kW, 200...240 V, single phase Variable speed drive ATV320...B 0.75 kW, 200...240 V, single phase Variable speed drive ATV320...B 1.1 kW, 200...240 V, single phase Variable speed drive ATV320...B 1.5 kW, 200...240 V, single phase Variable speed drive ATV320...B 2.2 kW, 200...240 V, single phase Variable speed drive ATV320...B 0.37 kW, 380...500 V, three phase Variable speed drive ATV320...B 0.55 kW, 380...500 V, three phase Variable speed drive ATV320...B 0.75 kW, 380...500 V, three phase Variable speed drive ATV320...B 1.1 kW, 380...500 V, three phase Variable speed drive ATV320...B 1.5 kW, 380...500 V, three phase Variable speed drive ATV320...B 2.2 kW, 380...500 V, three phase Variable speed drive ATV320...B 3 kW, 380...500 V, three phase Variable speed drive ATV320...B 4 kW, 380...500 V, three phase

Ordering and shipping details

Category	US1CP4B22149
Discount Schedule	CP4B
GTIN	3606480613135
Returnability	No
Country of origin	ID

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.874 in (7.300 cm)
Package 1 Width	6.693 in (17.000 cm)
Package 1 Length	9.055 in (23.000 cm)
Package 1 Weight	9.947 oz (282.000 g)
Unit Type of Package 2	P06
Number of Units in Package 2	60
Package 2 Height	29.528 in (75.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	59.348 lb(US) (26.920 kg)