Product data sheet

Specifications



power cable - between servomotor BSH and servodrive - 4 x 6 mm² + 2 x 1 mm² -15m

VW3M5105R150

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Power cable
Accessory / Separate Part Type	Preassembled power cordset
Accessory / separate part category	Connection accessories
Product compatibility	Servo motor BMH, 1 7.5 in (190 mm))B2 IEC 60204-1 Servo motor BMH, 2 7.5 in (190 mm))E IEC 60204-1 Servo motor BMH, 3 7.5 in (190 mm))E IEC 60204-1 Servo motor BMH, 3 8.07 in (205 mm))B2 IEC 60204-1
Accessory / separate part destination	Between servo motor and servo drive
Range Compatibility	Lexium 32
Cable length	49.2 ft (15 m)
Cable composition	4 x 6 mm² + 2 x 1 mm²

Complementary

Electrical connection	Free end servo drive side Connector - industrial M40 servo motor side
Product Weight	20.9 lb(US) (9.5 kg)

Ordering and shipping details

Category	US1PC5118263
Discount Schedule	PC51
GTIN	3606485263885
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.00 in (10.16 cm)
Package 1 Width	17.50 in (44.45 cm)
Package 1 Length	18.50 in (46.99 cm)
Package weight(Lbs)	20.920 lb(US) (9.489 kg)

Contractual warranty

Warranty (in months)	18

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**526 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**53 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**464 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**9 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	Compliant
REACh Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**Yes**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	**No**