# Product data sheet

Specifications



## Wall mounted enclosure, PanelSeT S3X, stainless steel 316L, plain door, 600x600x250mm, IP66

NSYS3X6625H

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range** | Spacial |
| **Product name** | Spacial S3X |
| **enclosure type** | Multi-purpose |
| **category** | Compact enclosure |
| **nominal height** | 23.6 in (600 mm) |
| **nominal width** | 23.6 in (600 mm) |
| **nominal depth** | 9.8 in (250 mm) |
| **product installation** | Wall-mounting |
| **Device composition** | 1 body<br>1 door<br>2 lock door<br>2 perforated vertical profile drilled door |

## Complementary

| | |
|---|---|
| **Body type** | Single piece body, cross-shaped structure<br>Gutter shaped front rail |
| **Door type** | Solid |
| **Number of doors** | Front face 1 |
| **Door opening side** | Reversible 120 °) |
| **Lock type** | 2 points lock, 3 mm double-bar |
| **Mounting plate description** | Without mounting plate |
| **Type of gland plate** | Without gland plate |
| **Accessibility for operation** | Front |
| **Removable parts** | Door by hinges |
| **Material** | Lock zamak<br>Hinge stainless steel<br>Body and door stainless steel 316L |
| **Surface finish** | Body and door Scotch-Brite® brushed<br>Lock chromium plated |
| **Product Weight** | 30.9 lb(US) (14 kg) |

## Environment

| | |
|---|---|
| **Standards** | IEC 62208<br>UL<br>CUL |
| **Product Certifications** | CAN/CSA 22<br>UL 508 type A |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **IP degree of protection** | IP66 IEC 60529 |
| **IK degree of protection** | IK10 IEC 62262 |
| **Environmental characteristic** | Specific hygiene<br>Corrosive |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10ES180034 |
| **Discount Schedule** | 0ES1 |
| **GTIN** | 3606480155253 |
| **Returnability** | No |
| **Country of origin** | BG |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 10.630 in (27.000 cm) |
| **Package 1 Width** | 24.016 in (61.000 cm) |
| **Package 1 Length** | 24.016 in (61.000 cm) |
| **Package weight(Lbs)** | 30.865 lb(US) (14.000 kg) |
| **Unit Type of Package 2** | PAM |
| **Number of Units in Package 2** | 18 |
| **Package 2 Height** | 78.740 in (200.000 cm) |
| **Package 2 Width** | 39.370 in (100.000 cm) |
| **Package 2 Length** | 47.244 in (120.000 cm) |
| **Package 2 Weight** | 588.635 lb(US) (267.000 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **208 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **143 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **28 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0.7 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **0 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **37 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| SCIP Number | **E893f0a0-d2cc-4011-9425-3873dde70142** |
| EU RoHS Directive | **Compliant** |
| REACh Regulation | **Free of Substances of Very High Concern above the threshold** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |
| PVC free | **Yes** |
| Silicon free | **Yes** |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | **No** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | **No need of specific recycling operations** |
| Take-back | **No** |

Technical Illustration

**Dimensions**



Offer Marketing Illustration

**Product benefits / Features**

