# Product data sheet

Specifications



Discontinued - Service only

## Uniflair InRow SC, 300mm, Air Cooled, Self-contained 200-240V 60Hz

ACSC100

Discontinued on: Aug 31, 2023

To be end-of-service on: Sep 30, 2033

**Product availability: Stock - Normally stocked in distribution facility**

## Overview

| | |
|---|---|
| **Lead time** | Usually Ships within 2 Weeks |

## Main

| | |
|---|---|
| **Main Input Voltage** | 200 V<br>208 V<br>220 V<br>230 V<br>240 V |
| **Input Connection Type** | NEMA L6-20P |
| **Number of rack unit** | 42U |
| **Number of cables** | 1 |
| **Provided Equipment** | Exhaust duct kit<br>Installation guide<br>Operations and maintenance manual |

## General

| | |
|---|---|
| **Compressor Type** | Rotary |
| **Air Discharge Patterns** | Horizontal |
| **Intake Air** | Rear Return |
| **Refrigerant Charge** | 3 lb(US) (1.4 kg) |
| **air flow** | 1200 ft³/min (566.3 l/s) |
| **Inrush current** | 56 A |
| **Condensate Pump Capacity** | 1.3 Gal/hr(US) (0.005 m3/h) |

## Physical

| | |
|---|---|
| **Color** | Black |
| **Height** | 78.39 in (199.1 cm) |
| **Width** | 11.81 in (30 cm) |
| **Depth** | 42.09 in (106.9 cm) |
| **Net Weight** | 365.79 lb(US) (165.92 kg) |
| **Mounting preference** | No preference |
| **Mounting Mode** | Not rack-mountable |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Input

| | |
|---|---|
| **Input power** | 2940 W |
| **Input Frequency** | 60 Hz |

## Conformance

| | |
|---|---|
| **Product Certifications** | BSMI<br>UL Listed<br>VCCI<br>VDE |
| **Standards** | EN 55022 Class A<br>FCC Part 15 class A<br>ICES-003 |

## Environmental

| | |
|---|---|
| **Ambient Air Temperature for Storage** | 32…104 °F (0…40 °C) |
| **Storage Relative Humidity** | 0…95 % |
| **Storage altitude** | 0…15000 ft (0…4572 m) |
| **Acoustic level** | 80 dBA |

## Communications & Management

| | |
|---|---|
| **control panel** | Multi-function LCD status and control console |

## Ordering and shipping details

| | |
|---|---|
| **Category** | 11309-APC RESALE PRODUCTS |
| **Discount Schedule** | APC1 |
| **GTIN** | 731304246848 |
| **Returnability** | No |
| **Country of origin** | IN |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 84.88 in (215.6 cm) |
| **Package 1 Width** | 44.80 in (113.8 cm) |
| **Package 1 Length** | 30.00 in (76.2 cm) |
| **Package weight(Lbs)** | 476.2 lb(US) (216 kg) |

## Contractual warranty

| | |
|---|---|
| **Warranty** | 1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Use Better

#### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| EU RoHS Directive | **Not applicable, out of EU RoHS legal scope** |
| California proposition 65 | **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov** |

### Use Again

#### Repack and remanufacture

| | |
|---|---|
| Take-back | **No** |

Image of product / Alternate images

**Alternative**

