Product data sheet

Specifications



PowerLogic Remote display, color touchscreen, 192 x 192 mm for ION9200

METSERD192

Product availability: Stock - Normally stocked in distribution facility

Main

Range	PowerLogic
Product or Component Type	Remote display
Device Application	Human-machine dialogue application
Range compatibility	PowerLogic PowerLogic ION9000
Display Type	LCD touch screen

Complementary

Display colour	Color
Display Resolution	800 x 480 pixels
Display size	7 inch
Information Displayed	Energy consumption Voltage Power Harmonic distortion Frequency Current System alarm I/O status
Messages display capacity	Graphic objects (bargraph, button, light...)
Local signalling	Status LED Green) Alarm LED Red)
Control type	1 x push-button Touch screen
Connector Type	RJ45
Provided equipment	Mounting Hardware
Mounting Mode	Flush-mounted
Mounting support	Framework remote display
Width	7.8 in (197 mm)
Height	6.9 in (175 mm)
Projecting depth	1.08 in (27.5 mm)
Product Weight	10.6 oz (300 g)

Environment

IP degree of protection	IP65 IEC 60529
IK degree of protection	IK08
Relative humidity	5…95 %

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Operating altitude	0...9842.52 ft (0...3000 m)
Ambient Air Temperature for Operation	-13…140 °F (-25…60 °C)
Ambient Air Temperature for Storage	-40…185 °F (-40…85 °C)
Product Certifications	IEC IEEE

Ordering and shipping details

Category	US10PM109762
Discount Schedule	0PM1
GTIN	3606489555894
Returnability	No
Country of origin	CA

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.5 in (14.0 cm)
Package 1 Width	9.4 in (24.0 cm)
Package 1 Length	10.2 in (26.0 cm)
Package weight(Lbs)	3.5 lb(US) (1.6 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**634 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**589 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.1 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**44 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.9 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
SCIP Number	**593f15dc-c512-4cf6-ac2d-78a614f80e12**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**0**
Circularity Profile	End of Life Information
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**