

Product data sheet

Specifications



Bus coupler, TeSys island, 24VDC, 3A, Profibus DP

TPRBCPFB

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	TeSys
Product name	TeSys island
Device short name	TPRBC
Product or Component Type	Bus coupler
Communication Port Protocol	Profibus DP
Device presentation	Point of connection between a group of starters and an automation controller Management of the complete island up to 20 modules
Function Available	Full integration with SoMove for the control of the island One single 24V DC power supply for the complete island One fieldbus port for communication with an automation controller One service port with an embedded webserver for maintenance
Product compatibility	TPRST motor starter TPRSS SIL motor starter TPRPM power module TPRSM SIL interface module TPRVM voltage interface module TPRAN analog IO module TPRDG digital IO module
Integrated connection type	1 SUB-D 9 female Profibus DP, fieldbus port 1 RJ45 female Ethernet TCP/IP, service port 1 micro SD card port
Communication service	Type 3 data-link layer service Profibus DHCP client Ethernet TCP/IP SNTP client Ethernet TCP/IP
Local signalling	1 LED green/yellow PWR power supply status 1 LED green/red MS module status 1 LED green/red COM network status 1 LED green/red BS internal bus status 1 LED green/red SD SD card access (SD)
[Us] rated supply voltage	24 V DC
Supply voltage limits	20.4...28.8 V DC
Rated current	3 A maximum
Protection type	External fuse, 3 A fast power supply Reverse polarity protection power supply
Power dissipation in W	7 W maximum

Complementary

Cybersecurity	Achilles certified
Standards	EN/IEC 60947-4-1 CSA C22.2 No 61010-2-201 UL 61010-2-201 EN/IEC 61010-2-201

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	UL CSA EAC Achilles level 2 PNO
Mounting mode	Horizontal and vertical 35 mm symmetrical rail)
Connections - terminals	Power supply removable spring terminal block 2 0.004 in² (2.5 mm²) AWG 14)rigid or flexible
Width	2.0 in (50 mm)
Height	4.6 in (118 mm)
Depth	4.5 in (114 mm)
Product Weight	0.450 lb(US) (0.204 kg)

Environment

Ambient air temperature for storage	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Operation	14...140 °F (-10...60 °C)
Relative Humidity	5...95 %
Operating altitude	0...6561.68 ft (0...2000 m) without derating
IP degree of protection	IP20
Pollution degree	2
Protective treatment	TC
Fire resistance	1760 °F (960 °C) UL 94
Shock resistance	15 gn 11 ms) IEC 60068-2-27
Vibration resistance	1.5 mm peak to peak 3...13 Hz) IEC 60068-2-6 1 gn 13...200 Hz) IEC 60068-2-6
Electromagnetic compatibility	Electrostatic discharge, level 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF fields, level 3, 10 V/m, conforming to EN/IEC 61000-4-3 Communication: fast transients immunity test, level 3, 1 kV, conforming to EN/IEC 61000-4-4 Power supply: fast transients immunity test, level 3, 2 kV, conforming to EN/IEC 61000-4-4 Communication: surge immunity test (common mode), level 3, 1 kV, conforming to EN/IEC 61000-4-5 Power supply: surge immunity test (common mode), level 3, 2 kV, conforming to EN/IEC 61000-4-5

Ordering and shipping details

Category	US10I1222345
Discount Schedule	0I12
GTIN	3606489832735
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.559 in (6.500 cm)
Package 1 Width	5.315 in (13.500 cm)

Package 1 Length	6.102 in (15.500 cm)
Package weight(Lbs)	10.159 oz (288.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	12.015 lb(US) (5.450 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	737c99ce-bdba-4209-8b07-d1c5bfde8889
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Carbon black, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts & cables product

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.