

**UPC Code :** 078477495629

**Country Of Origin :** Mexico

# M5631-W

Lev-Lok Decora Plus Single-Pole Rocker Switch, Illuminated - Load OFF, Heavy-Duty Industrial Specification Grade, 20 Amp, 120/277 Volt AC, Modular, Self-Grounding - White
Mating Lev-Lok Wiring Module Required for Use

## Technical Information

### Material Specifications

**Actuator Material :** Polycarbonate

**At Rated Voltage :** 1 HP @ 120V, 2HP @ 240V

**Base Material :** Nylon

**Contact Material :** Silver-Alloy

**Frame Material :** Polycarbonate

**Ground Clips :** Brass

**Strap Material :** .046" Thick Galvanized Steel

### Warranty

**Amperage :** 20 A

**Dielectric Voltage :** Withstands 1500 V for 1 minute

**Endurance :** 30,000 cycles min

**Grounding :** Self-Grounding

**Overload UL20 Test :** 100 cycles of OL at 4.8 times rated current

**Temperature Rise :** Maximum 30° C Rise

**Voltage :** 120/277 VAC

**Warranty :** 10-Year Limited

### AC Horsepower Rating

**At Rated Voltage :** 1 HP @ 120V, 2HP @ 240V

**Flammability :** Rated V-2 per UL 94

**Operating Temperature :** -40°C to 60°C

### Electrical Specifications

**Actuator Material :** Polycarbonate

**Amperage :** 20 A

**Base Material :** Nylon

**Dielectric Voltage :** Withstands 1500 V for 1 minute

**Endurance :** 30,000 cycles min

**Frame Material :** Polycarbonate

**Ground Clips :** Brass

**Grounding :** Self-Grounding

**Overload UL20 Test :** 100 cycles of OL at 4.8 times rated current

**Strap Material :** .046" Thick Galvanized Steel

**Temperature Rise :** Maximum 30° C Rise

**Voltage :** 120/277 VAC

### Environmental Specifications

**Flammability :** Rated V-2 per UL 94

**Operating Temperature :** -40°C to 60°C

**Product ID :** Ratings are permanently marked on device

**Terminal Accom. :** Wiring Module

**Terminal ID :** Labeled on wiring module, switch is keyed to ensure proper installation

**Termination :** Modular

### Mechanical Specifications

**ANSI :** C-73

**Applicable Standards :** UL20, CSA C22.2 No. 111

**Certification/Listing :** cULus (File #E7458)

**Product ID :** Ratings are permanently marked on device

**RoHS :** Compliant

**Terminal Accom. :** Wiring Module

**Terminal ID :** Labeled on wiring module, switch is keyed to ensure proper installation

**Termination :** Modular

### Standards & Certifications

**ANSI :** C-73

**Applicable Standards :** UL20, CSA C22.2 No. 111

**Brand :** Lev-Lok Decora Plus

**Certification/Listing :** cULus (File #E7458)

**Color :** White

**Device Type :** Rocker Switch

**Feature 2 :** Illuminated - Load OFF

**Function :** Single-Pole

**Grade :** Heavy-Duty Industrial Specification Grade

**RoHS :** Compliant

### Product Features

**Brand :** Lev-Lok Decora Plus

**Color :** White

**Device Type :** Rocker Switch

**Feature 2 :** Illuminated - Load OFF

**Function :** Single-Pole

**Grade :** Heavy-Duty Industrial Specification Grade

**Patents***

| | |
|---|---|
| CA2655707 | US7666010 |
| CA2667092 | US8096818 |
| US7357652 | |

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

| JOB NAME: | CATALOG NUMBERS: | |
|---|---|---|
| | | |
| JOB NUMBER: | | |

**Leviton Manufacturing Co., Inc.**
201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

**Leviton S. de R.L. de C.V.**
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

ISO 9001 REGISTERED Quality Manufacturer

**Visit our Website at: www.leviton.com**
© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**
If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/