23034-A



UPC Code: 07847780906

Country Of Origin: Mexico

Item Description

20 Amp, 125 Volt, Non-NEMA, 3P, 3W, Locking Plug, Industrial Grade, Grounding, Power Interrupting Device - BLACK

Technical Information

Electrical Specifications

Grounding: Grounding

Amperage: 20 A

Voltage: 125 VAC

Pole: 3

Wire: 3

Dielectric Voltage: Withstands 2000V per UL498

Current Interrupting: Certified for current interrupting at full rated current

Temperature Rise: Max 30C after 50 cycles OL at 150 percent rated current

Environmental Specifications

Flammability: Rated V-0 per UL 94

Operating Temperature: -40°C to 105°C

Environment: Dry

Material Specifications

Body Material: Super Tough Nylon

Interior Material: Phenolic

Blades/Contacts: Solid Brass

Line Contacts: Brass

Terminal Screws: Brass 8-32

Grounding Screw: Brass 8-32

Assembly Screws: Steel, Zinc Plated

Cord-Clamp: Nylon

Mechanical Specifications

Terminal Accom.: 12-4 AWG

Product ID: Ratings are permanently marked on device

Product Features

Amperage: 20 A

Pole: 3

Cord Range: .250 - .656

Wire Gauge: 18-10 AWG

Body Material: Super Tough Nylon

Standards and Certifications: UL

Feature: Power Interrupting

Standards and Certifications

cULus: Listed

UL: 498

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.
201 North Service Road, Melville, NY 11747
Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx



Visit our Website at: www.leviton.com
© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.
If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/