Actual



Representative

**Catalog Number:** **APA-750**
**Product ID:** 7TAA007480R0014
**UPC Number:** 07511413363
**Status:** Active

Aluminum Solid Pin Terminals Center Pin Style with Insulating EDPM Rubber Boot, Wire Size 750 kcmil, Tin Plated, Overall Length 3.79 Inches (96.27mm), Die Code 115, Yellow

- Tooth design to provide greater holding force. One piece connector design for increased reliability.
- UL Listed with T&B and competitor application tooling.
- Pin designed to have greater cross-sectional area than conductor. EPDM rubber or PVC boot provided to eliminate the need for any taping.
- Termination of aluminum or copper conductors to mechanical lugs.

## UNSPSC Specifications

| | |
|---|---|
| UNSPSC | 39121405 Cable or wire lug |
| IGCC | 4532 Cable or wire lug |
| Brand Name | Blackburn |
| Type | Pin Adapters |
| Special Features | Pin Adapters |
| Application | Termination of aluminum or copper conductors to mechanical lugs. |
| Voltage Rating | 600V |
| Material | Aluminum |
| Color | Yellow |

## Packaging

| | |
|---|---|
| Outer Quantity | 3 |
| Outer Dimensions (inches) | 7.5x6.8x4.7 |
| Weight Uom | 44.5 lbs. per 100 |

## Documents / Support Tools

| | |
|---|---|
| SDS US 1 | sds-00041-tb2 |
| Technical Data Sheet CA | Available on Website |

**For further technical assistance, please contact us...**

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com