

Service Entrance Splices

T&B Catalog Number: IKL35
UPC Number: 78378605021
Status: Active
Description:

Aluminum 5 1/2" Service Entrance Compression Splice for Wire Range - End A: 1/0 ASCR, 2/0 Str., 1/0 Str. Compact, Red, End B: 2 ASCR, 1-2 Str., Red, Die: 840

Features

	Use for combinations of aluminum-to-aluminum and aluminum-to-copper conductors. Can be used as a low-cost reducing sleeve.
	Concave caps seal out dirt but are easily pierced when inserting conductor. Prefilled with Oxide Inhibitor.
	Color-coded and marked for easy identification.
	Standards compliant. Meets ANSI C119.4 requirements. Connectors are RUS listed.

General

Insulation Type	Insulated
Material	Aluminum
Barrel Length	Longer Length
Conductor Range A ASCR	1/0
Conductor Range A Str./Sol.	2/0 Str., 1/0 Str. Compact
Conductor Range B ASCR	2
Conductor Range B Str./Sol.	1-2 Str.
Conductor A Color	Yellow
Conductor B Color	Red

Dimension Information

Length (inches)	5.5
Conductor A Diameter Max.	0.398
Conductor A Diameter Min.	0.365
Conductor B Diameter Max.	0.328
Conductor B Diameter Min.	0.268

Tooling

Die Series	840 Die Series
Hydraulic Dies	B49EA, 840 U-K840, U-249
Mechanical Dies	BY37, 840 W-K840, TX

Packaging

T&B Inner Pack	25
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	22.67 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com