

Representative

Catalog Number: **4464FC**
Product ID: 7TAA057550R0000
UPC Number: 70891719838
Status: A

Delayed Reaction Angled Surface Mount Receptacle, 20 Amp, 2 Pole 3 Wire, XP Flap Cap

North American Specifications (UNSPSC)

UNSPSC	39121404 Electrical sleeves
IGCC	4528 Electrical sleeves
Brand Name	Russellstoll
Type	Russellstoll Hazardous-Duty Plugs, Receptacles and Interlocks
Special Features	Circuit-breaking receptacles, plugs and connectors ensure complete circuit breaking under full rated loads. Equipment grounding is provided by means of a separate pole that makes contact before and breaks contact after the circuit poles. The delayed action operation sequence is as follows: Insert plug, turn left push in to make electrical contact then turn right to prevent accidental disconnection. To with-draw plug, the reverse procedure is followed, which provides time for extinction of the arc and cooling before the plug can be completely withdrawn.
Application	For use in hazardous materials environment like: Gas or Vapor, Dust, or Fibers/Flyings
Number Of Poles	2
Number Of Wires	3
Amperage Rating	20 Amp
Material	Cast Aluminum

European Specifications (ETIM)

ETIM	EC001322 Round socket/plug for high currents
Amperage	20A
Number of poles	2

Packaging

Inner Dimensions (inches)	7.12x7.12x6
Outer Quantity	1
Outer Dimensions (inches)	16x16x16
Weight Uom	3.75 lbs. Each

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com