



Actual

Catalog Number: SB50/10M
Product ID: 7TCA296040R0080
UPC Number: 78621024503
EAN Number: 05020963061998
Status: A

Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 50mm, Outside Diameter 56.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 10 Meters, Galvanised Steel Core and Overbraid

- Very high UV resistance
- High flexibility
- High fatigue life
- High mechanical strength, high abrasion resistance
- Inherent low fire hazard and halogen free
- Enhanced EMI screen rating
- Industrial

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Adaptaflex
Type	Low Fire Hazard Conduit
Special Features	Very High UV Protection and High Fatigue Life
Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Trade Size	1-1/2 in
Outside Diameter	56.0 mm
Inside Diameter	48.4 mm
Length	10 m
Radius	90 mm
Flexibility	High
Material	Galvanized Steel Core and Overbraid

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	50mm
Outer diameter	56mm
Inner diameter	48.4mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Steel wire, galvanized
Operating temperature	-50-+300°C
Degree of protection (IP)	IP40
Weight	0.939kg/m
Colour	Metallic
Bending strength	Flexible

Packaging

Outer Quantity	1
Outer Dimensions (inches)	17x37x17
Weight Uom	20.7 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

ABB Installation Products - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com