

Aluminum Lug
T&B Catalog Number:

ALS44

UPC Number: 78378605090
Status: Active
Description:

Aluminum Two-Hole Lug - Straight Long Barrel, Wire Range 636 26/7,, 715 54/7, 666 26/7, 54/7 ASCR, 750-800 Str., 900 Compact, 1/2 Inch Bolt Size, Blind-End, Hydraulic Dies: 1 1/2, 6024, 125H, CSA 30

Features

	Complete die and crimp information clearly indented on each lug. Install with standard tools and dies.
	NEMA standard mounting holes. Use 1/2 inch mounting hardware for all sizes.
	Prefilled with oxide inhibitor.

General

Style	ALS
Material	Aluminum
Conductor Range - ASCR	636 26/7,, 715 54/7, 666 26/7, 54/7
Conductor Range - Stranded	750-800
Conductor Range - Compact	900

Dimension Information

Length (inches)	7 1/4
Width (inches)	1 5/8
T (inches)	5/8
Diameter Min. (inches)	1.031
Diameter Max. (inches)	0.990

Tooling

Hydraulic Dies	1 1/2, 6024, 125H, CSA 30

Packaging

Package in Units	20
T&B Sold in UOM	Each
T&B Weight Per UOM	81.75 lbs. per 100

Notes

	Hole Spacing 1 3/4 inches.
	Available tin-plated (add suffix P to catalog number).

Certifications

RoHS Compliance	Yes

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com