ALLIED MOULDED PRODUCTS, Inc.
222 N Union Street • Bryan, OH 43506
Ph: (800) 722-2679 • Fx: (800) 237-7269
Email: sales@alliedmoulded.com
www.alliedmoulded.com

9361-EC2



VIDEO

Product Description

Single gang electrical box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™
Catalog #: 9361-EC2

Height: 3-1/4 in.
Width: 2-3/8 in.
Depth: 2-7/8 in.
Volume: 16 cu. in.
Type of Installation: Old Work
Wall Box
Number of Gangs: 1

Carton Quantity: 100
Carton Weight: 33 lb.

UPC: 085339105602
UNSPSC: 39121308
Country of Origin: United States of America

FEATURES

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

APPLICATION

Old work residential construction 2 HR fire resistive walls

STANDARDS

ANSI / UL 514C: File No. E30594

FIRE CLASSIFICATION

Fire Test of Building Construction Materials
ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)
Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less
Shall be separated by a horizontal distance of not less than 3 inches
Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

MATERIAL

Fiberglass reinforced polyester BMC

MOUNTING

Metal ears

ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

Plated carbon steel clamp and fasteners

© 2018 Allied Moulded Products, Inc.