BURNDY

GZ2658, Mechanical Grounding Connector, Copper Cable to Bar



By Burndy
Catalog # GZ2658

Cast Cu Alloy Ground Clamp, Cable to Bar, #3 - 2/0 AWG Str, 5/8" Bolt

Features

- Rated for Direct Burial in earth or concrete
- UL 467 Listed for the US and Canadian Markets

Application

For Joining A Wide Range Of Copper Cable To Bar, Direct Burial In Concrete Or Ground

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	• 3 • 2 • 1 • 1/0 • 2/0
Conductor - Copper Str Size Range	3 AWG - 2/0 AWG

Dimensions

Dimension - L Length Overall mm	48 mm
Dimension - Height fraction	2-1/4
Dimension - Height inch	2.25 in
Dimension - Height mm	57.2 mm
Dimension - Width fraction	1-3/4 in
Dimension - Width inch	1.75 in
Dimension - Width mm	44 mm
Dimension - Length Overall inch	1.88 in

Force Related

Installation Torque Recommended in-lb	660 LBS/in

General

Material Type - Screw	DURIUM™ Silicon Bronze
Sub Brand	MECHANICAL CONNECTOR
Plated	N
Construction Material - Main	Copper
Type	GZ
UPC 12 Digit	781810990148
UPC 14 Digit GTIN	00781810990148
Material	Copper
Plating Type	Unplated
UPC	781810990148

Logistics

Carton Quantity	1
Pallet Quantity	1

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved