
CT250500RQ0, Cable Tie, 250 Lb Tensile, UV Black, Releasable



By Burndy
Catalog # CT250500RQ0

Nylon UNIRAP™ Cable Tie - 250 Lb. Tensile Strength (Releasable)

Features

- Releasable Cable Tie
- Specially suitable for prototype construction or temporary installation
- Also suitable where service often requires adding or subtracting wires from an existing bundle

Application

For Use Where Service Requires Adding Or Subtracting Wires From An Existing Wire Bundle

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
Certification - 94V0 Rated	N
UL Listed	No
Certification - UV Rated	Yes

Dimensions

Dimension - L Length Overall mm	559 mm
Width	0.5 in
Dimension - Width inch	0.50 in
Dimension - Width mm	13 mm
Length	20 in
Dimension - Bundle Diameter Max inch	6.00
Dimension - Length Overall inch	22 in

Force Related

Rating - Minimum Tensile Strength lbs	250

General

Trade Name	UNIRAP™
Sub Brand	UNIRAP,CABLE TIE
Series	UNIRAP™ Series
Color	Black
Type	Heavy Duty Releasable
UPC 14 Digit GTIN	00781810334836
Material	NYLON 6/6
UPC	781810334836

Logistics

Minimum Pack Quantity	25
Carton Quantity	500
Pallet Quantity	14000

Operational

Operating Temperature Celcius Max	85 °C
Operating Temperature Celcius Min	-40 °C

Product Assets

Catalog [English]

© 2026 Hubbell Incorporated. All rights reserved