BGBL4, Aluminum Lay-in Lug, 4-14 AWG



By Burndy
Catalog # BGBL4

Tin Plated Aluminum Lay-in Lug, 4-14 AWG, 1/4" Zinc Plated Terminal Screw, #10 Stud

Features

- UL486B Listed, AL9CU Rated for copper and aluminum conductor combinations up to 90°C
- UL Recognized for grounding and bonding
- Lay-in feature eases installation

Application

For Copper And Aluminum Conductor Combinations Up To 90 DEG C

Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Industry Standard(s)	UL 486A-B
Standards - Industry Standards Met	UL 486A-B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Copper Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - AL Str Size	8 AWG;6 AWG;4 AWG
Conductor - AL Str Size Range	8 AWG-4 AWG
Conductor - Copper Solid Size	14 AWG;13 AWG;12 AWG;11 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - Copper Solid Size Range	14 AWG-4 AWG
Conductor - Copper Str Size Range	14 AWG - 4 AWG
Conductor Type	AL C Str-Size;CU C Str-Size;CU C Solid-Size

Dimensions

Dimension - L Length Overall mm	27 mm
Dimension - Pad Width inch	0.38 in
Dimension - Height fraction	7/9 in
Dimension - Height inch	0.78 in
Dimension - Height mm	19.8 mm
Dimension - Hole Size inch	0.22 in
Dimension - Hole Size mm	6 mm
Hex Size	Slot
Dimension - Length Overall inch	1.07 in
Dimension - D inch	0.62 in
Dimension - N inch	0.19 in

Force Related

Installation Torque Recommended in-lb	35 LBS/in

General

Trade Name	QIKLUG™
Material Type - Screw	Steel - Zinc Plated
Sub Brand	QIKLUG
Physical Attribute - Screw Type	Slot
Plated	Y
Type	BGBL, Lay-In
UPC 12 Digit	781810124857
UPC 14 Digit GTIN	00781810124857
Material	Aluminum
Plating Type	Tin
UPC	781810124857

Logistics

Minimum Pack Quantity	1
Carton Quantity	2400
Pallet Quantity	1

Operational

Temperature Rating	194

Product Assets

Catalog [English]

© 2025 Hubbell Incorporated. All rights reserved